

Always. Reliable. Tight.

Connection options for the inside/outside of buildings

SYSTEM OVERVIEW

HSI 150/KES-M 150


INSIDE OF BUILDING



Rubber technology

split rubber press seal for cables

1x Ø 36 – 70 mm (HSI 150-DG-1/36-70) or
1x Ø 70 – 112 mm (HSI 150-DG-1/70-112) or
3x Ø 24 – 54 mm (HSI 150-DG-3/24-54) or
6x Ø 10 – 36 mm (HSI 150-DG-6/10-36)



Shrink-sleeve for cables

3x Ø 22 – 56 mm HSI 150-D3/58
or 7x Ø 12 – 31 mm HSI 150-D7/33
(Heat shrink sleeves)



Shrink-sleeve for cables

1x Ø 25 – 78 mm (HSI 150-D1/80)
(Heat shrink sleeves)



Rubber technology for retrofit sealing split rubber press seal for cables


(HRD 150/160-G-z/d) max. 3x Ø 60 mm
or 5x Ø 47 mm or 9x Ø 33 mm
(recommended for HSI 150-GSM 110/X,
HSI 150-GSM 125/X, HSI 150-GSM 160/X)




HVS fire protection pads for cables

S90 insulation with system HSS-150
Cert. no. 19.15.1906 acc. to DIN 4102-9
(can be used in every HSI 150 installation variant)

WALL




HSI 150-K/X
Single wall insert



HSI 150-K2/X
Double wall insert




HSI 150-DFK
Flange for doweling in front of core drillings
Ø_{max.} = 150 mm




HSI 150-GSM 110/ or 125/ or 160/x
Single wall insert with plug-in socket sleeve

OUTSIDE OF BUILDING




Corrugated cable ducts (sleeve method with clip rings)

HSI 150-M168WR (Ø 160 mm)
HSI 150-M110WR, HSI 150-M125WR




Smooth cable ducts (plug-in socket)

HSI 150-D110/125/160 GSM (Ø 110, Ø 125, Ø 160 mm)




Cable entry system

KES-M 150-D (spiral hose Hateflex 14150 Ø 168 mm)




SEGMENTO for cables

from Ø 5 – 31 mm



Rubber technology split rubber press seal for cables

1x Ø 36 – 70 mm (HSI 150-DG-1/36-70) or
1x Ø 70 – 112 mm (HSI 150-DG-1/70-112) or
3x Ø 24 – 54 mm (HSI 150-DG-3/24-54) or
6x Ø 10 – 36 mm (HSI 150-DG-6/10-36)



Shrink-sleeves for cables

3x Ø 22 – 56 mm HSI 150-D3/58
or 7x Ø 12 – 31 mm HSI 150-D7/33
(Heat shrink sleeves, also available as cold shrink)

for pipes

corrugated cable ducts Ø 75 – 125 mm (Cold shrink sleeves) HSI 150-D110-KS, HSI 150-D125-KS



Rubber technology rubber press seal for cables

(HRD 150/160-G-z/d) max. 3x Ø 60 mm or 5x Ø 47 mm
or 9x Ø 33 mm or HRD 150/160-2SGi (individual)



Smooth cable ducts

Ø 110, Ø 125, Ø 160 mm

Other special solutions on request!



Hauff-Technik GmbH & Co. KG

Robert-Bosch-Straße 9
89568 Hermaringen, GERMANY

Tel. +49 7322 1333-0
Fax +49 7322 1333-999

office@hauff-technik.de