

Always. Reliable. Tight.

Connection options for the inside/outside of buildings


SYSTEM OVERVIEW

HSI 90/KES-M 90

INSIDE OF BUILDING

WALL

OUTSIDE OF BUILDING




Shrink-sleeves for cables
3x Ø12 - Ø30 mm HSI 90-D3/32
or 6x Ø8 - Ø18 mm HSI 90-D6/20
(Heat shrink sleeves)




Shrink-sleeves for cables
1x Ø25 - 72 mm HSI 90-D1/75
(Heat shrink sleeves)




Rubber technology for retrofit cable sealing
HRD94-1G-z/d (for HSI 90) configuration for example:
max. 3x Ø30 mm
or 5x Ø22 mm
or 9x Ø13 mm



HSI 90-K/X
Single wall insert



HSI 90-K2/X
Double wall insert




HSI 90-DF
Flange for do-
weling in front
of core drillings
Ø max. = 90 mm




Smooth cable ducts
Ø90 with sleeve system HSI 90-M90
Ø110 with sleeve system HSI 90-M110



Corrugated cable ducts
Ø75 Cold shrink-sleeves HSI 90-D75 KS
Ø90 Sleeve system with clip rings
HSI 90-M90 WR
Ø110 Sleeve system with clip rings
HSI 90-M110 WR



Cable entry system
KES-M 90-D (spiral hose Hateflex 14090
Ø102mm)



Shrink-sleeves for cables
3x Ø12 - 30 mm HSI 90-D3/32
or 6x Ø8 - 18 mm HSI 90-D6/20
(Heat shrink sleeves,
also available as cold shrink)



Shrink-sleeves for cables
1x Ø25 - 72 mm HSI 90-D1/75
or 1x Ø38 - 72 mm HSI 90-D1/75 KS

KS= cold-shrink sleeve (recommended for corrugated pipe connections)
Other special solutions on request!



Hauff-Technik GmbH & Co. KG

Robert-Bosch-Straße 9
89568 Hermaringen, GERMANY

Tel. +49 7322 1333-0
Fax +49 7322 1333-999

office@hauff-technik.de