

Always. Reliable. Tight.

For cable und pipe (duct) seals

# SYSTEM OVERVIEW

## PRESS SEALS

INSIDE OF BUILDING	WALL	OUTSIDE OF BUILDING
	<p>HRD...-SG</p> <p>e. g. core drilling or wall sleeve (ZVR)</p>	<p>Standard press seal for cables split with segmented ring technology HRD...-SG</p> <ul style="list-style-type: none"> <li>• sealing width 40 mm</li> <li>• for quick adaptation to cable diameter on-site</li> </ul>
	<p>HSN/HSD/HSDD</p> <p>Core drilling or fibre cement wall sleeve (FZR.../FZR...-G)</p>	<p>Standard press seals for pipes installed in fibre cement pipe (closed FZR.../split FZR...G) or core drilling holes</p> <ul style="list-style-type: none"> <li>• HSN = sealing width 20 mm</li> <li>• HSD = sealing width 40 mm</li> <li>• HSDD = sealing width 80 mm</li> </ul>
	<p>HRD...-2(1)-(G)-F-z/d</p> <p>Core drilling or wall sleeve (ZVR)</p>	<p>HRD...-2(1)-(G)-F-z/d individual press seal closed/split with overlapping flange</p> <ul style="list-style-type: none"> <li>• sealing width 30 mm (1) non-pressing water</li> <li>• sealing width 60 mm (2) pressing water</li> </ul>
	<p>Core drilling or wall sleeve (ZVR)</p>	<p>ADS sealing set e.g. for corrugated cable ducts with ISO ring and clip rings inside cementcoated wall sleeve ZVR...</p>

**Always. Reliable. Tight.**

For cable und pipe (duct) seals

# SYSTEM OVERVIEW

## PRESS SEALS

INSIDE OF BUILDING	WALL	OUTSIDE OF BUILDING
<p>HRD...-1(G)-z/d individual press seal closed/split (G)</p> <ul style="list-style-type: none"> <li>sealing width 30 mm (1) non-pressing water</li> </ul>		<p>Sealing in front of the wall flange (HRD...F closed/HRD-FG split) with press seal HRD...-2(1)-(G)-z/d individual press seal closed/split (G)</p> <ul style="list-style-type: none"> <li>sealing width 30 mm (1) non-pressing water</li> <li>sealing width 60 mm (2) pressing water</li> </ul>
<p>HRD...-2(G)-z/ individual press seal closed/split (G)</p> <ul style="list-style-type: none"> <li>sealing width 60 mm (2) pressing water</li> </ul>		<p>Flange wall sleeve for buildings with sealing membranes in acc. with DIN 18195, Part 9 (black tank) with HRD...-2(1)-(G)-z/d individual press seal closed/split (G)</p> <ul style="list-style-type: none"> <li>sealing width 30 mm (1) non-pressing water</li> <li>sealing width 60 mm (2) pressing water</li> </ul>

Other special solutions on request!

**Hauff-Technik GmbH & Co. KG**

Robert-Bosch-Straße 9  
89568 Hermaringen, GERMANY

Tel. +49 7322 1333-0  
Fax +49 7322 1333-999

office@hauff-technik.de