

Sello de tubería modular – Cadena articulada GKD

TABLA DE SELECCIÓN

SELLO DE TUBERÍA MODULAR – CADENA ARTICULADA GKD – TABLA DE SELECCIÓN					
Ø _i -Apertura interior en el muro (mm)	Ø _a -Tubería exterior de suministro (mm)		Número de segmentos	Tipo GKD	Profundidad de instalación mínima
	desde	hasta			
100	58	63	6	300	100
125	73	78	8	315	100
	79	88	8	300	100
150	98	103	10	315	100
	104	113	10	300	100
200	108	117	7	475	150
	148	152	14	315	100
	153	153	15	315	100
	154	160	13	300	100
	161	163	14	300	100
250	153	166	9	475	150
	167	167	10	475	150
	169	177	7	400	150
	178	189	7	425	125
	190	202	9	325	110
	203	203	19	315	100
	204	213	17	300	100
300	157	167	7	500	165
	168	176	8	500	165
	178	184	8	525	165
	185	195	10	575	165
	196	203	8	440	150
	203	203	11	475	150
	204	208	8	440	150
	204	217	12	475	150
	218	227	9	400	150
	228	242	9	425	125
	243	252	11	325	110
	253	253	23	315	100
	254	263	21	300	100

Sello de tubería modular – Cadena articulada GKD

TABLA DE SELECCIÓN

SELLO DE TUBERÍA MODULAR – CADENA ARTICULADA GKD – TABLA DE SELECCIÓN					
Ø _i -Apertura interior en el muro (mm)	Ø _a -Tubería exterior de suministro (mm)		Número de segmentos	Tipo GKD	Profundidad de instalación mínima
	desde	hasta			
350	207	222	9	500	165
	223	234	9	525	165
	235	245	12	575	165
	246	252	9	440	150
	253	260	10	440	150
	261	266	14	475	150
	264	277	10	400	150
	278	292	11	425	125
	293	302	13	325	110
	303	303	27	315	100
	304	313	25	300	100
400	257	276	11	500	165
	277	284	11	525	165
	285	295	14	575	165
	296	310	11	440	150
	311	313	16	475	150
	314	329	12	400	150
	330	341	12	425	125
	342	342	13	425	125
	343	352	15	325	110
	353	353	31	315	100
	354	360	28	300	100
450	307	326	12	500	165
	327	332	12	525	165
	333	334	13	525	165
	334	345	16	575	165
	346	360	13	440	150
	361	367	19	475	150
	364	377	14	400	150
	378	392	14	425	125
	390	402	17	325	110
	398	403	35	315	100
	404	413	32	300	100

Sello de tubería modular – Cadena articulada GKD

TABLA DE SELECCIÓN

SELLO DE TUBERÍA MODULAR – CADENA ARTICULADA GKD – TABLA DE SELECCIÓN					
Ø _i -Apertura interior en el muro (mm)	Ø _a -Tubería exterior de suministro (mm)		Número de segmentos	Tipo GKD	Profundidad de instalación mínima
	desde	hasta			
500	332	346	13	650	165
	357	376	14	500	165
	374	384	14	525	165
	384	384	17	575	165
	385	400	18	575	165
	396	410	14	440	150
	403	417	21	475	150
	414	427	15	400	150
	428	442	16	425	125
	440	452	19	325	110
	448	453	39	315	100
	454	463	36	300	100
	350	370	9	615	205
550	382	396	15	650	165
	407	417	15	500	150
	418	426	16	500	150
	423	434	16	525	165
	434	435	19	575	165
	436	450	20	575	165
	446	460	16	440	150
	453	467	23	475	150
	464	477	17	400	150
	478	488	17	425	125
	489	492	18	425	125
	490	502	21	325	110

Sello de tubería modular – Cadena articulada GKD

TABLA DE SELECCIÓN

SELLO DE TUBERÍA MODULAR – CADENA ARTICULADA GKD – TABLA DE SELECCIÓN					
Ø _i -Apertura interior en el muro (mm)	Ø _a -Tubería exterior de suministro (mm)		Número de segmentos	Tipo GKD	Profundidad de instalación mínima
	desde	hasta			
600	400	420	10	615	205
	432	446	16	650	165
	457	476	17	500	165
	473	484	17	525	165
	484	486	21	575	165
	487	500	22	575	165
	496	510	17	440	150
	503	516	25	475	150
	517	517	26	475	150
	514	527	19	400	150
	528	542	19	425	125
	540	552	23	325	110
	540	552	23	325	110
650	450	470	11	615	205
	482	496	18	650	165
	507	526	19	500	165
	523	534	19	525	165
	534	537	23	575	165
	538	550	24	575	165
	546	560	19	440	150
	553	554	27	475	150
	555	567	28	475	150
	564	576	20	400	150
	577	577	21	400	150
	578	592	21	425	125
	590	602	25	325	110

Our sales people are ready to help you with any questions concerning our products and services.

auswahltabelle_akd_es_190516

www.hauff-technik.de