

Single-line building package


For buildings without a basement

ESH Basic FUBO BHP6m

: 3030474698, GTIN: 4052487240734



- Duct system checked for pressure tightness
- easy integration of the vapour barrier using the adhesive ribbon





Advantages:

- quick and easy installation
- Continuous duct connection up to the main supply lines at the edge of the property possible

Scope of delivery:

- 1 piece basic unit, including adhesive ribbon
- 1 piece Height-adjustable installation fixture with flanges as water barrier
- 1 piece spiral hose 14078, including sleeve pipe and mounted 3-ribbed seal
- 1 piece ESH Basic MBK SR1 seal insert
- 1 piece sealing element for drinking water SDW 1x32/40/50
- 1 piece sealing element for electricity SDE 1x26-29/36-39/43-46/48-51
- 1 piece sleeve cap MS78U 1x24-52 for electricity or water
- 1 piece GMT35 lubricant



Properties:

- DVGW-certified
- Variable height adaptation to the finished floor level
- 50-mm surrounding flange for connecting the vapour barrier

Application range:

- DIN 18533 W1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Tightness:

• gastight and watertight to 1.0 bar

Tests/Standards:

• DVGW VP 601

Hose length (m): 6.0 Packing unit: 1



office@hauff-technik.de