Seal insert for basic insert

ESH Basic MBK SR1

Article no.: 3030473652, GTIN: 4052487241229

- **all-around smooth surface for optimum connection of the finished flooring**

Gastight and watertight building entry for gas, water, power or telecommunications services for buildings without a basement. The building entry is installed in the ESH Basic FUBO EBT SR1 basic unit.

Picture may differ from selected product

FACTS

Scope of delivery:

- 1 piece of seal insert
- 4 nail screws for fixing the sealing insert
- 2 pieces of self-tapping screws M8x45 and washers for sealing service lines

Dimensions:

- Width: 135 mm
- Length: 135 mm
- Height: 283 mm

Properties:

- DVGW-certified
- Also required: gas valve or closed sealing element

Material:

- Anchor plate: glass fibre reinforced polyamide
- Pipe: glass-fibre-reinforced polyamide with TPE
- Screws: stainless steel V2A (AISI 304L)

Tightness:

- gastight and watertight to 1.0 bar

Tests/Standards:

- DVGW VP 601

FEATURES

Item: Dichteinsatz für Rohbauteil

PICTURES

Hauff-Technik GmbH & Co. KG
Robert-Bosch-Straße 9
89568 Hermaringen, GERMANY

Tel. +49 7322 1333-0
Fax +49 7322 1333-999

office@hauff-technik.de