

# Membrane injection system


for buildings without a basement

## 2LINE MIS25 1x6-13 PRO

: 3030477964, GTIN: 4052487242905



- **Controlled RESINATOR resin discharge thanks to proven membrane injection system**
- **Tool-free assembly with RESINATOR double syringe**
- **Horizontal or inclined installation up to 45° inclination**



For reliable sealing of fibre optic cables.

### Advantages:

- Sealing in all common wall types (DIN 18533/WU concrete)
- Minimum RESINATOR resin quantity thanks to adhesive collar
- Small opening diameter  $\varnothing_i$
- Quick to assemble in just a few minutes

### Scope of delivery:

- 1 piece 2LINE MIS25
- 1 piece RESINATOR dual syringe, 25 ml
- 1 piece wall terminator element

### Dimensions:

- Area of application: 1 fibre-optic cable with  $\varnothing_a$
- for drill holes  $\varnothing_i$ : 25 mm
- for wall thicknesses starting from 150 mm

## Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2
- 1 fibre-optic cable with  $\text{Øa}$  6 - 13 mm

## Material:

- Membrane sleeve: TPE
- Foil flange: Aluminium-plastic composite foil with butyl rubber
- Wall terminator element: PCFR

## Tightness:

- gastight and watertight to 1.0 bar

Number of cables/medium: 1  
Suitable for medium pipe OD (mm): 6-13 MM

