

Membrane injection system


for buildings without a basement

2LINE MIS25 2x7-10 PRO

Article no.: 3030564551



- **controlled RESINATOR resin discharge thanks to proven membrane injection system**
- **tool-free assembly with RESINATOR double syringe**
- **Horizontal or angled installation up to 45° angle**



Picture may differ from selected product

For reliable sealing of fibre optic cables. For installation in all standard wall types to DIN 18533 W1.1-E, W1.2-E, W2.1-E and waterproof concrete according to DIN 1045. Includes 2-component resin RESINATOR.

FACTS

Advantages:

- Sealing in all common wall types (DIN 18533/WU concrete)
- Minimal amount of RESINATOR resin required thanks to adhesive sleeve
- Small opening diameter Øi
- Quick to assemble in just a few minutes

Scope of delivery:

- 1 piece of 2LINE MIS25
- 1 piece of RESINATOR dual syringe, 25 ml
- 1 piece of wall terminator element

Dimensions:

- for drill holes Øi: 25 mm
- for wall thicknesses starting from 150 mm

Application range:

- Water exposure class DIN 18533: W1-E and W2.1-E
- Waterproof concrete stress class 1 and 2
- Application area: 2 fiber optic cables with Øa 7-10 mm or 1 fiber optic cable with Øa 6 - 13 mm or 1 fiber optic cable with Øa 12-16 mm

Material:

- Membrane sleeve: TPE
- Foil flange: Aluminium-plastic composite foil with butyl rubber
- Wall terminator element: PCFR

Tightness:

- gastight and watertight to 1.0 bar

FEATURES

Number of cables/medium: 2
suitable for medium pipe OD (mm): 7-10

PICTURES

