

Plastic spiral hose

for cable entry system

Hateflex14150/15000

Article no.: 3030589939, GTIN: 4052487247818



- **flexible plastic spiral hose (peak compressive strength class 450 N DIN EN 61386-24)**
- **a pressure-tight cable entry system (for up to 2.5 bar external pressure) can be created using the associated connection components.**



Picture may differ from selected product

Flexible and very rugged plastic spiral hose. A pressure-tight cable entry system can be created with the associated connection components.

FACTS

Advantages:

- Empty conduit without sleeve available in lengths of up to 25 m
- Empty conduit system that can be built over
- Smooth inner surface for gentle cable pulling

Scope of delivery:

- Coils in lengths of 25 m (special lengths are available in 0.5 m sections)
- includes closing cover

Dimensions:

- ID: 151 mm \pm 1 mm
- OD: 166 mm \pm 1 mm

Properties:

- Peak compressive strength: Class 450N (DIN EN 61386-24)
- Minimum bending radius: 900 mm
- Weight: 4500 g/m
- Installation temperature from +5° to + 50°C
- Smooth inner surface for gentle cable pulling
- Weather-proof, UV-resistant and rot-resistant
- Resistant to brine and seawater

Material:

- Hard PVC/soft PVC

Tightness:

- gastight and watertight to 2.5 bar

FEATURES

Length (m): 15.0

PICTURES

