

Membrane injection system

for buildings with a basement

MIS60D E BL1300 SET1

Article no.: 3030453449, GTIN: 4052487240017



- **universal building entry with membrane injection system for drill holes in the most common types of wall**
- **controlled ejection of resin through slit membrane hose**
- **sealing lips ensure gentle seal for media lines**



Picture may differ from selected product

For existing buildings with a basement for reliable sealing of standard water lines.

FACTS

Advantages:

- Quick to assemble in just a few minutes
- Not necessary to restore basement seal to DIN 18533
- Variety of seal inserts for variable configuration

Scope of delivery:

- 10 pieces of MIS 60D including pre-mounted seal insert
- 10 pieces of wall terminator element (only for communication variant)
- 10 pieces of wall collar (only with electricity variant)
- 10 pieces 2-component resin Resinator, 150 ml



Dimensions:

- For core drills Ø: 62 - 65 mm
- For wall thicknesses: from 200 to 1200 mm

Application range:

- Water exposure class DIN 18533: W1-E and W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Flange, seal insert, counter-bearing and adapter: EPDM
- Sealing tape: butyl
- Resin filler hose: PE
- Wall collar: PE
- Pipe: PVC-U
- Wall terminator element: Flame-retardant polycarbonate

Tightness:

- gastight and watertight to 1.0 bar
- radon tight

FEATURES

Number of cables/medium:	1 1 1 3 4
suitable for medium pipe OD (mm):	24-30 18-24 12-18 6-12 10 5-7
wall thickness (mm):	900 - 1.200

PICTURES



ACCESSORIES REQUIRED



Quick tensioning device



Cartridge gun