# Earthing fixed point
## with weld groove

# HEA A M12/50

Article no.: 1700300500, GTIN: 4052487124140

- **patented twist resistance provided by special contour of contact washer**

For earthing connection via weld groove, for installation flush with formwork. An earthing connection can be made with the thread in the conductor core. The HEA-A is used primarily in prefabricated construction.

Picture may differ from selected product

# FACTS

## Advantages:

- Watertight connection thread (blind hole)
- Resistant to corrosion

## Scope of delivery:

- 1 piece of eat-resistant protective foil

## Dimensions:

- Conductor core: round, Ø 25 mm
- Contact washer: Ø 72 mm
- Groove for weld connection for round steel: 10 - 12 mm
- Distance between contact washer and weld groove: 40/50 or 70 mm

## Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Conductor core and contact washers: stainless steel V4A (AISI 316L)
- Weld connection with groove: St37

## Tests/Standards:

- Short-circuit-tested to VDE 0101
- EN 50522

# FEATURES

Distance shuttering - reinforcement: 50

Hauff-Technik GmbH & Co. KG
Robert-Bosch-Straße 9
89568 Hermaringen, GERMANY

Tel. +49 7322 1333-0
Fax +49 7322 1333-999

office@hauff-technik.de