

# Flexible earthing entry

## HEA PF M12/3000

: 1700060060, GTIN: 4052487136822



- **Patented twist resistance provided by special contour of contact washer**



With flexible steel cable for positioning earthing connections which can be adjusted both up and down and from side to side. A cross-clamp (accessories) provides an ideal means of making a reinforcement connection.

### Advantages:

- Flexible cross-clamp connection in concrete is possible
- Shifting of connection positions, set in concrete in several sections
- Water barrier for tightness with concrete
- Watertight M12/M16 connection thread on both sides (blind hole)
- Resistant to corrosion

### Scope of delivery:

- 2 pieces Protective covers with 4 nail holes

### Dimensions:

- Conductor core: round, Ø 25 mm
- Contact washer: Ø 72 mm
- Steel cable: Ø 10 mm

### Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Conductor core and contact washers: stainless steel V4A (AISI 316L)
- Steel cable: galvanised
- Water barrier: NBR
- Protective covers: PE

## Tests/Standards:

- DIN 18014
- DIN EN 62305-3
- VDE 0185-305-3 (with lightning protection application)

Threaded bolt: M12  
wall thickness  
(mm): 3000