

Fire protection kit S90

For core drills and wall sleeves

HSS150 KB FR HRD

Article no.: 5030010033, GTIN: 4052487233545



- **special assembly pockets for the assembly of pads on one side**
- **special assembly pockets for the assembly of pads on one side**



Picture may differ from selected product

Gastight and watertight fire barrier meeting the requirements of fire resistance class S90 in accordance with DIN 4102-9 for installation in core drills and/or plastic wall sleeves for walls. The seal is created with the HRD press seal. The barrier is approved for use with all types of cable in wall openings up to \varnothing 300 mm.

FACTS

Advantages:

- High degree of flexibility as regards subsequent assignment
- No additional wall attachments necessary
- No limits on individual cable diameters
- Weatherproof fire-stop pads

Scope of delivery:

- Wall openings up to \varnothing 100 mm: 1 set of HVS pads for full assignment (without cable): 2x HVS-K-250, 3x HVS-KB-60
- Wall openings up to \varnothing 150 mm: 1 set of HVS pads for full assignment (without cable): 2x HVS-K-400, 3x HVS-K-250, 3x HVS-KB-60
- Stainless steel clamping strap
- 1 piece of Identification sign

Dimensions:

- Barrier thickness: min. 280 mm
- Wall thickness at and above: 150 mm
- For core drills ID: 70 - 300 mm
- For plastic wall sleeves ID: 80 - 300 mm

Tests/Standards:

- DIBT approval Z-19.15-1906 to DIN 4102-9

FEATURES

Wall sleeve/core drilled hole ID (mm): 150

PICTURES



ACCESSORIES REQUIRED



Lubricant



Assembly plate for fire-stop pads