

Fire protection kit S90

for HSI150 system cover

HSS150 HSI150

: 5030010030, GTIN: 4052487233613



- **Fire protection S90 combined with system covers**

- **Special assembly pockets for the assembly of pads on one side**



Gastight and watertight fire barrier meeting the requirements of fire resistance class S90 in accordance with DIN 4102-9 for installation in the HSI150 system for walls. The seal is created with system covers. The barrier is approved for use with all types of cable in walls.

Advantages:

- Fire protection for HSI150 cable entry
- High degree of flexibility as regards subsequent assignment
- No additional wall attachments necessary
- No limits on individual cable diameters
- Weatherproof fire-stop pads
- Approval for packages with HSI 150 up to 2 x 6

Scope of delivery:

- 1 set of HVS pads for full assignment without cable: 1x HVS-K-720, 1x HVS-K-400, 4x HVS-K-250/2, 4x HVS-KB-60
- Stainless steel clamping strap
- 1 piece Identification sign

Dimensions:

- Barrier thickness: min. 440 mm
- Wall thickness at and above: 240 mm
- Maximum package size: 430 x 1270 mm (2x6)

Tests/Standards:

- DIBT approval Z-19.15-1906 to DIN 4102-9

Wall sleeve/core drilled hole ID (mm): 150



Lubricant



Flexible socket wrench



Assembly plate for fire-stop pads