

# Fire protection kit S90

for HSI150 press seal

HSS150 HSI150 HRD

: 5030010031, GTIN: 4052487233583



- **Fire protection S90 combined with HRD 150/160 press seal**
- **Special assembly pockets for the assembly of pads on one side**



Gastight and watertight fire barrier meeting the requirements of fire resistance class S90 in accordance with DIN 4102-9 for installation in the HSI150 system for walls. The seal is created with the HRD press seal. The barrier is approved for use with all types of cable in walls.

## Advantages:

- Fire protection for HSI150 cable entry
- No additional wall attachments necessary
- No limits on individual cable diameters
- Weatherproof fire-stop pads
- Approval for packages with HSI 150 up to 2 x 6

## Scope of delivery:

- 1 set of HVS pads for full assignment (without cable): 2x HVS-K-400, 3x HVS-K-250, 3x HVS-KB-60
- Stainless steel clamping strap
- 1 piece Identification sign

## Dimensions:

- Wall thickness at and above: 150 mm
- Barrier thickness: min. 280 mm
- Maximum package size: 430 x 1270 mm (2x6)

## Tests/Standards:

- DIBT approval Z-19.15-1906 to DIN 4102-9

Wall sleeve/core drilled hole ID  
(mm):

150



Lubricant



Flexible socket wrench



Assembly plate for fire-stop pads