

Standard press seal

with infinitely super segmented ring technology

HSD150 SSG 1x70-112 b40 A2/EPDM55

: 3030300064, GTIN: 4052487129015



- **optical and tangible installation security due to integrated control opening**
- **Integrated super segmented ring technology for individual adjustment to cable diameter on site**
- **Segments with exact diameter marking**



For sealing of newly to install pipes or already installed pipes inside core drilled holes or wall sleeves. Infinitely adjustable to cable diameters on site.

Advantages:

- Split as standard for retrofit installation
- All manner of material combinations are available for tailor-made applications
- Available from stock



Dimensions:

- Sealing width up to Ø 250 mm: 40 mm
- Sealing width for Ø 300 mm: 50 mm

Properties:

- FHRK-certified
- U-profile: maximum stability for press segments

Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EDPM or NBR

Tightness:

- gastight and watertight
- radon tight

| | |
|--|--------|
| Wall sleeve/core drilled hole ID (mm): | 150 |
| Openings: | 1 |
| Carrier pipe \varnothing_a (mm): | 70-112 |
| Packing unit: | 1 |

