

# Standard press seal

with infinitely super segmented ring technology

## HSD200 SSG 1x110-162 b40 A4/EPDM55

: 3030300070, GTIN: 4052487224604



- **optical and tangible installation security due to integrated control opening**
- **Integrated super segmented ring technology for individual adjustment to cable diameter on site**
- **Segments with exact diameter marking**



For sealing of newly to install pipes or already installed pipes inside core drilled holes or wall sleeves. Infinitely adjustable to cable diameters on site.

### Advantages:

- Split as standard for retrofit installation
- All manner of material combinations are available for tailor-made applications
- Available from stock



### Dimensions:

- Sealing width up to Ø 250 mm: 40 mm
- Sealing width for Ø 300 mm: 50 mm

### Properties:

- FHRK-certified
- U-profile: maximum stability for press segments

## Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EDPM or NBR

## Tightness:

- gastight and watertight
- radon tight

|  |         |
|--|---------|
| Wall sleeve/core drilled hole ID (mm): | 200     |
| Openings:                              | 1       |
| Carrier pipe $\varnothing_a$ (mm):     | 110-162 |
| Packing unit:                          | 15      |

