

# Standard press seal

with infinitely super segmented ring technology

## HSD250 SSG 1x159-211 b40 A4/EPDM55

Article no.: 3030430482, GTIN: 4052487238663



- **optical and tangible installation security due to integrated control opening**
- **integrated super segmented ring technology for individual adjustment to cable diameter on site**
- **segments with exact diameter marking**

For sealing of newly to install pipes or already installed pipes inside core drilled holes or wall sleeves. Infinitely adjustable to cable diameters on site.



Picture may differ from selected product

## FACTS

### Advantages:

- Split as standard for retrofit installation
- All manner of material combinations are available for tailor-made applications
- available from stock

### Dimensions:

- Sealing width up to Ø 250 mm: 40 mm
- Sealing width for Ø 300 mm: 50 mm

### Properties:

- FHRK-certified
- U-profile: maximum stability for press segments



## Application range:

- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EDPM or NBR

## Tightness:

- gastight and watertight
- radon tight

## FEATURES

Wall sleeve/core drilled hole ID (mm):	250
Openings:	1
Carrier pipe $\varnothing$ (mm):	159-211
Packing unit:	4

## PICTURES

