

Outer sealing element module 4

for multi-line building entry systems for district heating basic variant 1

FLFA1x300/80/0 DIN18533 A2

: 2500400007, GTIN: 4052487062381

Outer sealing element for MSH Basic - district heating - BV 1 with fixed/loose flange for buildings with a basement with waterproof sheeting for standing/pressing water load case to DIN 18533, W2.2-E. Suitable for holding bitumen or foil waterproof sheeting.



Advantages:

- quick and easy installation

Scope of delivery:

- 1 piece Fixed/loose flange for dowelling
- 6 pieces wall fastenings SXR 10x80

Dimensions:

- Fixed flange OD: 630 mm
- Loose flange OD: 620 mm
- Thickness of fixed flange: 10 mm
- Thickness of loose flange: 10 mm

Properties:

- For buildings with a basement to DIN 18195 Part 6
- Holds waterproof sheeting (bitumen or foil)

Application range:

- Waterproof concrete stress class 1

Material:

- Stainless steel V2A (AISI 304L)

Tightness:

- gastight and watertight to 1.5 bar

Wall sleeve ID (mm) D1:	300
Fixed flange OD (mm) D2:	630
Loose flange OD (mm) D3:	620
Wall sleeve wall thickness (mm) S:	2



Outer sealing element module 1