

# Standard press seal

with segmented ring technology

HRD100 SG 2x8-30 3x4-16,5 b40 A2/EPDM50

: 2700103500, GTIN: 4052487000154



- **Segmented ring technology for adjustment to three or five different pipe diameters on site**

For sealing a water line or a power cable and communications lines in core drills or wall sleeves. Split design for sealing new cables to be installed or cables that have already been laid.



## Advantages:

- Empty openings are blind sealed ex works
- Split seal for retrofit installation
- Available from stock

## Scope of delivery:

- Blind plugs
- 1 piece Lubricating stick

## Dimensions:

- Sealing width: 40 mm
- Press plates: 5 mm

## Properties:

- FHRK-certified



## Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Press plates, screws, nuts and washers: rust-free stainless steel V2A (AISI 304L), (V4A (AISI 316L) on request)
- Rubber: EPDM

## Tightness:

- gastight and watertight
- radon tight

Wall sleeve/core drilled hole ID (mm):	100
Number of cables/medium overall:	5
Openings:	2 3
Carrier pipe $\varnothing_a$ (mm):	8-30 4-16,5

