

# Standard press seal

with super segmented ring technology and polymer press plates

## HRK200 SSG 3x40-72 b40 PAGF/A4/EPDM55

: 3030300050, GTIN: 4052487134576



- **Integrated segmented ring technology for individual adjustment to cable diameters on site**

- **Press plates have form-fit connections**

For sealing a water line or a power cable and communications lines in core drills or wall sleeves. Split design for sealing new cables to be installed or cables that have already been laid.



### Advantages:

- Available from stock

### Scope of delivery:

- Blind plug (if there is more than one cable entry)
- 1 piece Knife
- 1 piece Lubricating stick

### Dimensions:

- Sealing width: 40 mm

### Properties:

- FHRK-certified



## Application range:

- DIN 18533 W1-E, DIN 18533 W2.1-E, DIN 18533 W2.2-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

## Material:

- Press plates: glass fibre reinforced polyamide
- Rubber: EPDM
- Screws and nuts: rust-free stainless steel V4A (AISI 316L)

## Tightness:

- gastight and watertight
- radon tight

|  |       |
|--|-------|
| Wall sleeve/core drilled hole ID (mm): | 200   |
| Openings:                              | 3     |
| Carrier pipe $\varnothing_a$ (mm):     | 40-72 |
| Packing unit:                          | 1     |

