

# Single-line building package

for buildings with a basement

# ESH PolySafe BHP

: 3030300035, GTIN: 4052487223515



 optical and tangible installation security due to integrated control opening

Building package in the form of a single-line building entry system suitable for gas, water or power supplies - can used in all common types of wall.



## **Advantages:**

- quick and easy installation
- Continuous duct connection possible

### **Scope of delivery:**

- 1 piece Single-service building entry system ESH PolySafe GV1
- 1 piece Outer sealing element ESH PolySafe M6.2
- 1 piece Insulation disk MSH PolySafe M3
- 1 piece sealing element for drinking water SDW 1x32/40/50
- 1 piece sealing element for electricity SDE 1x26-29/36-39/43-46/48-51
- 1 piece sleeve cap MS78U 1x24-52 for electricity or water
- 1 piece Pipe connection/extension set 4-piece
- 1 piece GMT35 lubricant

#### **Dimensions:**

- Compatible with core drill/wall sleeve ID: 99 103 mm
- Sleeve pipe OD: 75 mm, 600 mm long
- maximum wall thickness: 500 mm





# **Properties:**

DVGW-certified

# **Application range:**

- DIN 18533 W1-E, DIN 18533 W2.1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

## **Tightness:**

- gastight and watertight to 1.0 bar
- radon tight

### **Tests/Standards:**

• DVGW VP 601

Packing unit: 10



Tel. +49 7322 1333-0

Fax +49 7322 1333-999