Membrane injection system

for buildings with a basement

MIS60ND 4x5-7 BL1300 Set10

Article no.: 3030380186, GTIN: 4052487229692

Picture may differ from selected product

- **no groundwork at the property**
- **universal building entry with membrane injection system for drill holes in the most common types of wall**
- **controlled ejection of resin through slit membrane hose**

For reliable sealing of micropipes/ fibre optic cables, telecommunications cables or power cables. Can be used for uncontrolled drilling rockets.

FACTS

Advantages:

- sealing lips ensure gentle seal for media lines
- Variety of pre-mounted seal inserts for variable configuration

Scope of delivery:

- 1 packing unit:
- 10 pieces of MIS 60ND
- 10 pieces of wall terminator element (only for communication variant)
- 10 pieces of wall collar (only with electricity variant)
- 10 pieces 2-component resin RESINATOR, 150 ml
- 1 piece of quick tensioning device MIS60 SVS
- 1 piece of core drill hole cleaning brush MIS REB

Dimensions:

- For core drills Ø: 62 - 65 mm
- For wall thicknesses: from 200 to 1200 mm

Application range:

- Water exposure class DIN 18533: W1-E
- Waterproof concrete stress class 1, waterproof concrete stress class 2

Material:

- Flange, seal insert and counter-bearing: EPDM
- Resin filler hose: PE
- Wall terminator element: Flame-retardant polycarbonate
- Pipe: PVC-U
- Wall collar: PE
- Fast arrangement fixture: glass fibre reinforced polyamide/ABS

Tightness:

- gastight and watertight to 1.0 bar

FEATURES

Number of cables/medium:	4
suitable for medium pipe OD (mm):	5 - 7
Overall lenght (mm):	1300
Wall thickness (mm):	200 - 1.200

Hauff-Technik GmbH & Co. KG
Robert-Bosch-Straße 9
89568 Hermaringen, GERMANY

Tel. +49 7322 1333-0
Fax +49 7322 1333-999

office@hauff-technik.de