

# Fixed/loose flange wall sleeve made from stainless steel

for setting in concrete for black tank according to DIN 18533

FLFE1x125/0/365 DIN18533 A2

Article no.: 2500125365

For setting in concrete or mortar in walls, ceilings or floors.



Picture may differ from selected product

## FACTS

### Advantages:

- Tailor-made designs can also be produced
- Also available with multiple entries and in a variety of diameters
- Installation flush with formwork

### Scope of delivery:

- 1 piece of fixed/loose flange wall sleeve
- Bolts and nuts M20 (DIN 18533)
- with closing covers on both sides

## Dimensions:

- Standard fixed flange  $\varnothing a$  equal to the relevant wall sleeve  $\varnothing i$  + approx. 330 mm (for one passage)

## Application range:

- Water exposure class DIN 18533: W1-E, W2.1-E and W2.2-E

## Material:

- Fixed/loose flange wall sleeve: stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Closing cover: PE

## Tightness:

- gastight and watertight

## FEATURES

|                                       |     |
|---------------------------------------|-----|
| Wall sleeve ID (mm) D1:               | 125 |
| Fixed flange OD (mm) D2:              | 450 |
| Loose flange OD (mm) D3:              | 440 |
| Wall sleeve wall thickness (mm)<br>S: | 2   |
| wall thickness (mm):                  | 365 |

## PICTURES



# ACCESSORIES REQUIRED



Rubber inlays