

Multi-line building package

for buildings with a basement

MSH PolySafe BHP

Article no.: 3030476028, GTIN: 4052487240949



- **integrated leak test equipment**
- **reliable installation due to front panel with integrated spirit level**
- **Visual and physical installation control thanks to integrated inspection opening**

For the collective feeding in and sealing of all supply lines (power, water, telecommunications, gas).



Picture may differ from selected product

FACTS

Advantages:

- Seals all supply lines through one entry
- Continuous duct connection up to the main supply lines at the property boundary possible
- All services are fed in and sealed separately
- The arrangement of the individual services is flexible



Scope of delivery:

- 1 piece of multi-line building entry system MSH PolySafe GV1
- 1 piece of external sealing element MSH PolySafe M6.2
- 1 piece of insulation disc MSH PolySafe M3
- 1 piece of sealing element for drinking water SDW 1x32/40/50
- 1 piece of sealing element for electricity SDE 1x26-29/36-39/43-46/48-51
- 1 piece of universal sealing element communications SDK 1x13-21+3x7-13+1x5-13
- 1 piece of blind sealing element SD0
- 1 piece of 16-piece pipe connection set (4 double sleeves DN75 + 12 profile seals DN75) RAS16
- 2 pieces sleeve caps MS78U 1x24-52 for electricity and water
- 1 piece of sleeve cap MS78K 1x13-21+3x7-13+1x5-12 for communications
- 1 piece of sleeve cap MS78 D0 for blind seal
- 2 pieces GMT35 lubricant

Dimensions:

- Compatible with core drill/wall sleeve: ID: 199 - 203 mm
- Maximum wall thickness: 500 mm (special lengths on request)

Properties:

- DVGW-certified

Application range:

- Water exposure class DIN 18533: W1-E and W2.1-E
- Waterproof concrete stress class 1 and 2

Tightness:

- gastight and watertight to 1.0 bar
- radon-proof

Tests/Standards:

- DVGW VP 601

FEATURES

Packing unit: 6

PICTURES

