

Universal wall sleeve

for any type of wall

UFR200/300 B

Article no.: 3030466854, GTIN: 4052487243179



- **printed scale for adjusting to specific wall thickness**
- **Flange for plastic-modified bitumen thick coatings**
- **Tested solution for use in pre-applied membrane sheet systems**
- **Can be used in all wall types with three sealing levels**



Picture may differ from selected product

Allows sealing in all wall types thanks to the combination of a flange and 3-ribbed seals. Can be cut to length on site to specific wall thickness using printed scale. For setting in concrete, closed on both sides ready for installation.

FACTS

Advantages:

- Suitable for the use of press seals
- Can be used in all types of walls including modular constructions
- Can be cut to length on site
- 3-ribbed seals can be adjusted on site
- light weight
- Simple installation in the formwork



Scope of delivery:

- 1 piece of wall sleeve with flange
- 3 pieces of 3-ribbed seal
- 2 pieces of closing covers

Dimensions:

- Flange all-around: 50mm
- Common wall thicknesses printed on the tube

Properties:

- FHRK-certified
- Ready for installation with closing cover
- Dimensionally stable
- resistant to cracking

Application range:

- Water exposure class DIN 18533: W1-E and W2.1-E
- Waterproof concrete stress class 1 and 2

Material:

- Pipe: PVC-U
- Flange: ABS
- 3-ribbed seals: EPDM
- Closing cover: PE

Tightness:

- gastight and watertight

FEATURES

Wall sleeve ID (mm):	200
Wall sleeve OD (mm):	214
flange edge dimension (mm):	336
flange surface dimension (mm):	311
Length (mm):	300

PICTURES

