

Floor drain with foil flange

BALF

Article no.: 3030551818, GTIN: 4052487247085



- **integrated odor trap bell**
- **Prevention of clogging of the drain tank through dirt trap screen**
- **Square foil flange**

Suitable for draining gray water in the floor area. Gas- and watertight connection to the base plate with an integrated lip seal. Includes foil flange for connection to a bituminous thick coating, weldable membrane, or vapour barrier.



Picture may differ from selected product

FACTS

Advantages:

- easy connection of the sealing or vapour barrier using a foil flange
- Class K3 – loadable up to 300 kg
- Top frame with sludge trap screen infinitely adjustable and rotatable from 30-70 mm
- Simplified cleaning and maintenance thanks to dirt trap screen

Scope of delivery:

- 1 piece drain body with foil flange
- 1 piece top frame
- 1 piece of sludge trap screen
- 1 piece of plastic grating
- 1 piece of odor seal
- 1 piece of construction time protection cover



Dimensions:

- Top frame: 150 x 150 mm
- Drain connection: DN 110 and DN 50
- Foil flange: 500 x 500 mm

Properties:

- Discharge rate: 1.79 l/s
- Resistant to hot water for short periods

Application range:

- Waterproof concrete stress class 1 and 2

Material:

- Base body: PP
- Drain grate: PA
- Lip seal: TPE
- Foil flange: EPDM

Tightness:

- pressure-rated up to 5,0 bar
- radon-proof

FEATURES

suitable for medium pipe OD
(mm):

110

PICTURES



ACCESSORIES REQUIRED

