

## Slab entry

BDF125 KG2000

Article no.: 3030551722, GTIN: 4052487246385



- **ready for installation in the slab**
- **Quick and easy installation**
- **includes closing cover**

For connecting KG-/HT-pipes. Gas- and watertight connection to the base plate with an integrated lip seal.



Picture may differ from selected product



# FACTS

## Advantages:

- no interruption of the waste water pipe system
- with push-in socket on one side to fit standard KG-/HT-pipes
- available in KG and KG2000
- Can be cut to length on site

## Scope of delivery:

- KG pipe with bonded lip seal
- KG2000 pipe with welded-on lip seal
- 1 piece of closing cover

## Dimensions:

- Pipe length: 500 mm

## Application range:

- Waterproof concrete stress class 1 and 2

## Material:

- KG pipe: PVC-U
- KG2000 pipe: PP
- Lip seal: TPE

## Tightness:

- pressure-rated up to 5,0 bar
- radon-proof

## Tests/Standards:

- KG pipes to DIN EN 13476-2
- KG2000 pipes to DIN EN 14758

# FEATURES

|                                   |        |
|-----------------------------------|--------|
| suitable for medium pipe OD (mm): | 125    |
| Type:                             | KG2000 |
| Packing unit:                     | 1      |