

# Single wall insert with foldable rubber sleeve

for setting in concrete and connecting cable ducts

HSI90 1x1 KMA94/63/400

Article no.: 3030576769



- thanks to the folding sleeve technique, no additional pipe connection components are necessary
- elastic and firmly supported connection due to increased insertion depth, even with deflection of the cable duct
- inside connection option for system seals for cables



Picture may differ from selected product

For the direct connection of cable ducts (exterior) and for connecting system seals for cables (interior).

## FACTS

### Advantages:

- defined insertion depth of the cable duct through the stop in the sleeve
- Available from wall thicknesses of 120 mm and above
- pressure-tight seal to the concrete through 3-ribbed seal, with two 3-ribbed seals from wall thicknesses of 150 mm and above

### Scope of delivery:

- 1 piece pressure-tight closing cover
- 1 piece blind cover
- 1 piece of clamping strap



## Dimensions:

- Frame dimensions: 145x 145 mm (per wall insert)

## Material:

- Wall insert: ABS
- Closing cover: ABS with EPDM seal
- Adapter pipe: PVC
- Sleeve: EPDM
- Clamping straps: W4
- Blind cover: PP

## Tightness:

- gastight and watertight
- radon-proof

## FEATURES

Wall thickness (mm):	400
Pipe OD (mm):	63