

Plastic spiral hose


for cable entry system

Hateflex14090/2000

Article no.: 3030590139, GTIN: 4052487247634



- **Flexible plastic spiral duct (peak compressive strength class 450N DIN EN 61386-24)**
- **A pressure-tight cable entry system (for up to 2.5 bar external pressure) can be created using the matching connection components.**



Flexible and very rugged duct A pressure-tight cable entry system can be created with the matching connection components.

Picture may differ from selected product

FACTS

Advantages:

- Single duct length of 25m without connection sleeves
- Constructible duct system
- Smooth inner surface for gentle cable pulling

Scope of delivery:

- Coils in lengths of 25 m (special lengths are available in 0.5 m sections)
- includes closing cover

Dimensions:

- ID: 91 mm \pm 1 mm
- OD: 104 mm \pm 1 mm

Properties:

- Peak compressive strength: 745 N
- Installation temperature: +5°C to +50°C
- Weight: 4000 g/m
- Resistant to brine and seawater
- Installation temperature from +5° to + 50°C
- Weather-proof, UV-resistant and rot-resistant
- Resistant to brine and seawater

Material:

- Hard PVC/soft PVC

Tightness:

- gastight and watertight to 2.5 bar

FEATURES

Length (m): 2.0

PICTURES

