

Membrane injection system

for buildings with a basement

MIS60D E BL1000 SET1

Article no.: 3030453433, GTIN: 4052487240000



- **universal building entry with membrane injection system for core holes in the most common types of wall**
- **Controlled resin discharge through slotted membrane hose**
- **sealing lips ensure gentle seal for cables/pipes**



Picture may differ from selected product

For existing buildings with a basement for reliable sealing of standard water pipes.

FACTS

Advantages:

- Quick to assemble in just a few minutes
- No repair of the basement waterproofing in accordance with DIN 18533 necessary
- Variable sealing configuration thanks to various sealing inserts

Scope of delivery:

- 1 piece of MIS60D including pre-mounted seal insert
- 1 piece of wall terminator element
- 1 piece of wall rosette



Dimensions:

- For core drills Ø: 62 - 65 mm
- For wall thicknesses: from 200 to 1200 mm

Application range:

- Water exposure class DIN 18533: W1-E and W2.1-E
- Waterproof concrete stress class 1 and 2

Material:

- Flange, seal insert, counter-bearing and adapter: EPDM
- Sealing tape: butyl
- Resin injection hose: PE
- Wall rosette: PE
- Pipe: PVC-U
- Wall terminator element: Flame-retardant polycarbonate

Tightness:

- gastight and watertight to 1.0 bar
- radon-proof

FEATURES

Number of cables/medium:	1 1 1 3 4
suitable for medium pipe OD (mm):	24-30 18-24 12-18 6-12 10 5-7
Wall thickness (mm):	200 - 900

PICTURES



ACCESSORIES REQUIRED



Cartridge gun



Quick tensioning device