

Sealing set

for corrugated cable ducts and pipes

WRD300 1x200 b60 A2/EPDM

Article no.: 1622300200, GTIN: 4052487043816



- **Visual and physical installation control thanks to integrated inspection opening**
- **Patented clip ring technology ensures equal pressure and prevents deformation**

For sealing corrugated cable ducts and pipes. The patented clip rings inserted into the corrugated profile prevent deformation and damage to the corrugated pipe and at the same time ensure equal pressure on the press seal. The supplied insulation ring is used to centre the corrugated pipe on the inside of the building and ensures a clean wall finish.



Picture may differ from selected product

FACTS

Scope of delivery:

- 1 piece of standard press seal HSD
- Stainless steel clip rings
- 1 piece of Insulation ring, split

Dimensions:

- Sealing width: 40, 60 or 80 mm (depending on corrugated pipe)

Properties:

- FHRK-certified
- Clip rings are manufactured according to the profile of the corrugated pipe



Application range:

- Waterproof concrete stress class 1 and 2

Material:

- All metal parts: stainless steel V2A (AISI 304L)
- Rubber seal: EPDM
- Insulation ring: Styrodur (XPS)

Tightness:

- gastight and watertight
- radon-proof

FEATURES

Wall sleeve/core drilled hole ID (mm):	300
Nominal width (mm):	200
Manufacturer:	Thermaflex
Type:	FLEXALEN
	600

PICTURES

