

# Sealing set

for corrugated cable ducts and pipes

## WRD125 1x75 b40 A2/EPDM

Article no.: 1622200075, GTIN: 4052487120166



- **Visual and physical installation control thanks to integrated inspection opening**
- **Patented clip ring technology ensures equal pressure and prevents deformation**

For sealing corrugated cable ducts and pipes. The patented clip rings inserted into the corrugated profile prevent deformation and damage to the corrugated pipe and at the same time ensure equal pressure on the press seal. The supplied insulation ring is used to centre the corrugated pipe on the inside of the building and ensures a clean wall finish.



Picture may differ from selected product

## FACTS

### Scope of delivery:

- 1 piece of standard press seal HSD
- Stainless steel clip rings
- 1 piece of Insulation ring, split

### Dimensions:

- Sealing width: 40, 60 or 80 mm (depending on corrugated pipe)

### Properties:

- FHRK-certified
- Clip rings are manufactured according to the profile of the corrugated pipe



## Application range:

- Waterproof concrete stress class 1 and 2

## Material:

- All metal parts: stainless steel V2A (AISI 304L)
- Rubber seal: EPDM
- Insulation ring: Styrodur (XPS)

## Tightness:

- gastight and watertight
- radon-proof

## FEATURES

Wall sleeve/core drilled hole ID (mm):	125
Nominal width (mm):	75
Manufacturer:	Thermaflex
Type:	FLEXALEN
	600

## PICTURES

