

# Earthing entry

## with connecting lug and cross-clamp

### HEA PK M16/160

Article no.: 1700031160, GTIN: 4052487206143



- **Patented anti-twist protection thanks to the special shape of the contact disc**

For installation flush with the formwork in waterproof concrete. Earthing connections can be made on the inside and outside with the thread on both sides. An earthing connection can be made to the wall using a lug with a cross clamp.



Picture may differ from selected product

## FACTS

### Advantages:

- Water barrier for tightness with concrete
- Watertight connection thread on both sides (blind hole)
- Resistant to corrosion

### Scope of delivery:

- 1 piece of cross-clamp for connecting reinforcement/foundation earthing
- 2 pieces of protective covers with 4 nail holes

### Dimensions:

- Conductor core: round, Ø 25 mm
- Conductor core connection: with M16 threaded bolt
- Contact washer: Ø 72 mm

### Application range:

- Waterproof concrete stress class 1 and 2

## Material:

- Conductor core and contact washers: stainless steel V4A (AISI 316L)
- Conductor core connection: St37 galvanised
- Water barrier: NBR
- Protective covers: PE
- Terminal lug with cross-clamp: St37

## Tests/Standards:

- DIN 18014
- DIN EN 62305-3
- VDE 0185-305-3 (with lightning protection application)

## FEATURES

Wall thickness                      160  
(mm):  
Threaded bolt:                      M16

## PICTURES

