

Flexible earthing entry

HEA PF M12/250

Article no.: 3030349947, GTIN: 4052487227759



- **Patented anti-twist protection thanks to the special shape of the contact disc**

With flexible steel wire, for offset positioning of earthing connections in the vertical and lateral position. A cross clamp (accessory) can be used to make an optional connection to the armouring.



Picture may differ from selected product

FACTS

Advantages:

- Flexible cross-clamp connection within the concrete possible
- Offsetting of the connection positions, concreting in several sections
- Water barrier for tightness with concrete
- Watertight M12/M16 connection thread on both sides (blind hole)
- Resistant to corrosion

Scope of delivery:

- 2 pieces of protective covers with 4 nail holes

Dimensions:

- Conductor core: round, Ø 25 mm
- Contact washer: Ø 72 mm
- Steel cable: Ø 10 mm

Application range:

- Waterproof concrete stress class 1 and 2

Material:

- Conductor core and contact washers: stainless steel V4A (AISI 316L)
- Steel cable: galvanised
- Water barrier: NBR
- Protective covers: PE

Tests/Standards:

- DIN 18014
- DIN EN 62305-3
- VDE 0185-305-3 (with lightning protection application)

FEATURES

Threaded bolt:	M12
Wall thickness (mm):	250