

Standard press seal

with stepped variable super segmented ring technology

HSD150 SSG 1x75/90/110 b40 A2/EPDM

Article no.: 3030300062, GTIN: 4052487121804



- **Visual and physical installation control thanks to integrated inspection opening**
- **integrated super segmented ring technology for individual adjustment to cable/pipe diameter on site**
- **Segments with diameter marking**

For sealing new or already installed pipes in core drill holes or wall sleeves. Can be adapted to the most common cable diameters on site.



Picture may differ from selected product

FACTS

Advantages:

- Split as standard Ø 100 mm
- Can be split on site at and above Ø 150 mm for retrofit installation
- Different material combinations available for customised applications
- available from stock

Dimensions:

- Sealing width: 40 mm

Properties:

- FHRK-certified
- U-profile: maximum stability for press segments



Application range:

- Waterproof concrete stress class 1 and 2

Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EPDM

Tightness:

- gastight and watertight
- radon-proof

FEATURES

| | |
|--|-----------|
| Wall sleeve/core drilled hole ID (mm): | 150 |
| Openings: | 1 |
| Carrier pipe Øa (mm): | 75/90/110 |
| Packing unit: | 1 |

PICTURES

