

Single wall insert

for setting in concrete

HSI150 1x1 K/120

Article no.: 3030303363, GTIN: 4052487222938



- **Double security with closing cover and blind plate for wall thicknesses from 70 to 150 mm**
- **injection molded 3-ribbed seal for pressure-tightness seal with concrete**
- **Quality seal: tightness from the factory. Option to check for accidental or unauthorized opening of the closing cover**

"For the gas-tight and watertight connection on one side of system seals for cables or cable ducts, providing high flexibility for future use."



Picture may differ from selected product

FACTS

Advantages:

- System seal can be connected (e.g. cable duct connection or cable seal)
- Packages can be created with frame connection system on site

Scope of delivery:

- 1 piece pressure-tight closing cover



Dimensions:

- Frame dimensions: 220x 220 mm
- Centre to centre distance: 210 mm
- Minimum wall thickness: 70 mm

Properties:

- FHRK-certified
- Blind plate for breaking through
- Entry remains pressure tight even if closing cover is removed

Application range:

- Waterproof concrete stress class 1 and 2

Material:

- Wall insert: ABS with TPE 3-ribbed seal
- Adapter pipe with blind plate: ABS or for wall thickness > 150 mm: PVC
- Closing cover: ABS with TPE seal

Tightness:

- gastight and watertight to 2.5 bar
- radon-proof

FEATURES

Wall thickness
(mm): 120

PICTURES

