

Fire protection kit S90

For core drills and wall sleeves

HSS100 KB FR HRD

Article no.: 5030010032, GTIN: 4052487233569



- **Fire protection S90 in combination with pressure-tight press seals**
- **One-sided installation of pads using special mounting pockets**

Gas- and watertight fire protection seal in accordance with fire resistance class S90 to DIN 4102-9 for installation in core drill holes or plastic wall sleeves. Sealing is performed using the HRD press seals. The protection is approved for all types of cable in wall openings up to Ø 300 mm.



Picture may differ from selected product

FACTS

Advantages:

- High flexibility for future cable installations
- No additional wall extensions necessary
- No limits on individual cable diameters
- Weatherproof fire-stop pads

Scope of delivery:

- Wall openings up to Ø 100 mm: 1 set of HVS pads for full assignment (without cable): 2x HVS-K-250, 3x HVS-KB-60
- Wall openings up to Ø 150 mm: 1 set of HVS pads for full assignment (without cable): 2x HVS-K-400, 3x HVS-K-250, 3x HVS-KB-60
- Stainless steel clamping strap
- 1 piece of Identification sign

Dimensions:

- Barrier thickness: min. 280 mm
- Wall thickness at and above: 150 mm
- For core drills ID: 70 - 300 mm
- For plastic wall sleeves ID: 80 - 300 mm

Tests/Standards:

- DIBT approval Z-19.15-1906 to DIN 4102-9

FEATURES

Wall sleeve/core drilled hole ID (mm): 100

PICTURES



ACCESSORIES REQUIRED



Assembly plate for fire-stop pads



Lubricant