

# Fire protection kit S90

for HSI150 system cover

## HSS150 HSI150

Article no.: 5030010030, GTIN: 4052487233606



- **fire protection S90 combined with system covers**
- **One-sided installation of pads using special mounting pockets**



Picture may differ from selected product

Gas-tight and watertight fire protection seal in accordance with fire resistance class S90 to DIN 4102-9 for installation in the HSI150 system for walls. Sealing is provided using system covers. The barrier is approved for use with all types of cable in walls.

## FACTS

### Advantages:

- Fire protection for HSI150 cable entry
- High flexibility for future cable installations
- No additional wall extensions necessary
- No limits on individual cable diameters
- Weatherproof fire-stop pads
- Approval for packages with HSI150 up to 2 x 6

### Scope of delivery:

- 1 set of HVS pads for full assignment without cable: 1x HVS-K-720, 1x HVS-K-400, 4x HVS-K-250/2, 4x HVS-KB-60
- Stainless steel clamping strap
- 1 piece of Identification sign

## Dimensions:

- Barrier thickness: min. 440 mm
- Wall thickness at and above: 240 mm
- Maximum package size: 430 x 1270 mm (2x6)

## Tests/Standards:

- DIBT approval Z-19.15-1906 to DIN 4102-9

## FEATURES

Wall sleeve/core drilled hole ID (mm): 150

## PICTURES



## ACCESSORIES REQUIRED



Assembly plate for fire-stop pads



Lubricant



Flexible socket wrench