

Fire protection kit S90

for HSI150 system cover

HSS150 HSI150

Article no.: 5030010030, GTIN: 4052487233606



- **fire protection S90 combined with system covers**
- **One-sided installation of pads using special mounting pockets**

Gas-tight and watertight fire protection seal in accordance with fire resistance class S90 to DIN 4102-9 for installation in the HSI150 system for walls. Sealing is provided using system covers. The barrier is approved for use with all types of cable in walls.



Picture may differ from selected product

FACTS

Advantages:

- Fire protection for HSI150 cable entry
- High flexibility for future cable installations
- No additional wall extensions necessary
- No limits on individual cable diameters
- Weatherproof fire-stop pads
- Approval for packages with HSI150 up to 2 x 6

Scope of delivery:

- 1 set of HVS pads for full assignment without cable: 1x HVS-K-720, 1x HVS-K-400, 4x HVS-K-250/2, 4x HVS-KB-60
- Stainless steel clamping strap
- 1 piece of Identification sign

Dimensions:

- Barrier thickness: min. 440 mm
- Wall thickness at and above: 240 mm
- Maximum package size: 430 x 1270 mm (2x6)

Tests/Standards:

- DIBT approval Z-19.15-1906 to DIN 4102-9

FEATURES

Wall sleeve/core drilled hole ID (mm): 150

PICTURES



ACCESSORIES REQUIRED



Assembly plate for fire-stop pads



Lubricant



Flexible socket wrench