

Standard press seal

with continuously variable super segment ring technology

HSD100 SSG 1x18-65 b40 A2/EPDM

Article no.: 3030300060, GTIN: 4052487165655



- **Visual and physical installation control thanks to integrated inspection opening**
- **integrated super segmented ring technology for individual adjustment to cable/pipe diameter on site**
- **Segments with diameter marking**

For sealing new or already installed pipes in core drill holes or wall sleeves. Continuously adjustable to cable diameter on site.



Picture may differ from selected product

FACTS

Advantages:

- Split as standard for retrofit installation
- Different material combinations available for customised applications
- available from stock

Dimensions:

- Sealing width up to Ø 250 mm: 40 mm
- Sealing width for Ø 300 mm: 50 mm

Properties:

- FHRK-certified
- U-profile: maximum stability for press segments



Application range:

- Waterproof concrete stress class 1 and 2

Material:

- Press plates, screws and nuts: rust-free stainless steel V2A (AISI 304L) or V4A (AISI 316L)
- Rubber: EDPM or NBR

Tightness:

- gastight and watertight
- radon-proof

FEATURES

Wall sleeve/core drilled hole ID (mm):	100
Openings:	1
Carrier pipe Øa (mm):	18-65
Packing unit:	1

PICTURES

