

# Outer sealing element module 6.2

for multi-line building entry system MSH PolySafe GV 1 and GV 2

## MSH PolySafe M6.2

Article no.: 1560000109, GTIN: 4052487163545



- **tested according to DIN 18533**
- **visual installation reliability due to built-in inspection opening**

Combined outer sealing element to supplement the multi-line building entry PolySafe in core drill holes in double/element walls for integration into existing damp-proofing. The sealing width of 90 mm provides a seal against both the concrete shells of the double/element wall and the pre-mixed concrete filling.



Picture may differ from selected product

## FACTS

### Advantages:

- Highly reliable thanks to sealing width of 90 mm
- Combined outer sealing element with outer flange

### Scope of delivery:

- 1 piece of outer sealing element module 6
- 1 piece of outer flange module 2 (pre-assembled)
- 2 pieces of spacers (pre-assembled)
- 8 pieces of attachment elements (pre-assembled)

## Dimensions:

- Øa: 275 mm
- Sealing width: 90 mm

## Application range:

- Water exposure class DIN 18533: W1-E and W2.1-E
- Waterproof concrete stress class 1 and 2

## Material:

- Glass fibre reinforced polyamide/EPDM/stainless steel V2A (AISI 304L)

## PICTURES

