

# Basic variant with inner seal

## for buildings with a basement

### ESH PolySafe GV1

Article no.: 1910000000, GTIN: 4052487162821



- **Visual and physical installation control thanks to integrated inspection opening**

Gasttight and watertight building entry with inner seal in 40 mm sealing width for buildings with a basement for gas, water, power or telecommunications services for installation in core drills or wall sleeves. As this is a modular system, the outer seal can be freely selected as appropriate for the type of wall.



Picture may differ from selected product

## FACTS

### Advantages:

- Quick and easy installation
- Modular design as appropriate for the type of wall
- Continuous duct connection possible

### Scope of delivery:

- 1 piece of octagonal inner sealing element with sleeve pipe DN 75
- 2 pieces of self-tapping screws M8x45 and washers for sealing service lines

### Dimensions:

- Sealing width: 40 mm
- Core drill/wall sleeve: ID 99 - 103 mm
- Sleeve pipe OD: 75 mm, 600 mm long
- Maximum wall thickness: 500 mm (special lengths on request)



## Properties:

- DVGW-certified
- Also required: gas valve or closed sealing element and external module

## Application range:

- Water exposure class DIN 18533: W1-E and W2.1-E
- Waterproof concrete stress class 1 and 2

## Material:

- Front plate: glass fibre reinforced polyamide
- Rubber: EPDM
- Sleeve pipe: PVC-U
- Screws: stainless steel V2A (AISI 304L)

## Tightness:

- gastight and watertight to 1.0 bar
- radon-proof

## Tests/Standards:

- DVGW VP 601

## PICTURES

