

# Standard press seal

with segmented ring technology

## HRD100 SG 1x22-50+1x5-12 b40 A2/EPDM

Article no.: 3030548511, GTIN: 4052487245401



- **Segmented ring technology for adjustment on-site to pipe diameters**

Press seal for sealing cables in core drills or sleeves Split design for sealing new installed cables or cables that have already been installed.



Picture may differ from selected product

## FACTS

### Advantages:

- Unused openings factory-sealed with blind plugs
- split seal for retrofit installation
- available from stock

### Scope of delivery:

- Blind plugs
- 1 piece of lubricant stick

### Dimensions:

- Sealing width: 40 mm
- Press plates: 5 mm



## Properties:

- FHRK-certified

## Application range:

- Water exposure class DIN 18533: W1-E, W2.1-E and W2.2-E
- Waterproof concrete stress class 1 and 2

## Material:

- Press plates, screws, nuts and washers: rust-free stainless steel V2A (AISI 304L), (V4A (AISI 316L) on request)
- Rubber: EPDM

## Tightness:

- gastight and watertight
- radon-proof

## FEATURES

Wall sleeve/core drilled hole ID (mm):	100
Number of cables/medium overall:	2
Openings:	1 1
Carrier pipe Øa (mm):	22-50 5-12

## PICTURES

