

# Standard press seal

with super segmented ring technology and polymer press plates

## HRK200 SSG 3x40-72 b40 PAGF/A4/EPDM

Article no.: 3030300050, GTIN: 4052487134576



- **integrated segmented ring technology for individual adjustment to cable diameters on site**
- **press plates have form-fit connections**

Press seal for sealing cables in core drills or sleeves Split design for sealing new installed cables or cables that have already been installed.



Picture may differ from selected product

## FACTS

### Advantages:

- available from stock

### Scope of delivery:

- Blind plug (for multiple cable entries)
- 1 piece of kniefe
- 1 piece of lubricant stick

### Dimensions:

- Sealing width: 40 mm



## Properties:

- FHRK-certified

## Application range:

- Water exposure class DIN 18533: W1-E, W2.1-E and W2.2-E
- Waterproof concrete stress class 1 and 2

## Material:

- Press plates: glass fibre reinforced polyamide
- Rubber: EPDM
- Screws and nuts: stainless steel V4A (AISI 316L)

## Tightness:

- gastight and watertight
- radon-proof

## FEATURES

Wall sleeve/core drilled hole ID (mm):	200
Openings:	3
Carrier pipe Øa (mm):	40-72
Packing unit:	1

## PICTURES

