

Standard press seal

with super segmented ring technology and polymer press plates

HRK150 SSG 3x24-54 b40 PAGF/A4/EPDM

Article no.: 1600101630, GTIN: 4052487129275



- **integrated segmented ring technology for individual adjustment to cable diameters on site**
- **press plates have form-fit connections**

Press seal for sealing cables in core drills or sleeves Split design for sealing new installed cables or cables that have already been installed.



Picture may differ from selected product

FACTS

Advantages:

- available from stock

Scope of delivery:

- Blind plug (for multiple cable entries)
- 1 piece of kniefe
- 1 piece of lubricant stick

Dimensions:

- Sealing width: 40 mm



Properties:

- FHRK-certified

Application range:

- Water exposure class DIN 18533: W1-E, W2.1-E and W2.2-E
- Waterproof concrete stress class 1 and 2

Material:

- Press plates: glass fibre reinforced polyamide
- Rubber: EPDM
- Screws and nuts: stainless steel V4A (AISI 316L)

Tightness:

- gastight and watertight
- radon-proof

FEATURES

| | |
|--|-------|
| Wall sleeve/core drilled hole ID (mm): | 150 |
| Openings: | 3 |
| Carrier pipe Øa (mm): | 24-54 |
| Packing unit: | 1 |

PICTURES

