

Universal wall sleeve

for any type of wall

UFR200/365

Article no.: 3030300262, GTIN: 4052487216272



- **Flange for plastic-modified bitumen thick coatings**
- **Tested solution for use in pre-applied membrane sheet systems**
- **Can be used in all wall types with three sealing levels**

Allows sealing in all wall types thanks to the combination of a flange and 3-ribbed seals. For setting in concrete, closed on both sides ready for installation.



Picture may differ from selected product

FACTS

Advantages:

- Suitable for the use of press seals
- Can be used for double element walls
- Other lengths on request
- Can be cut to length on site
- 3-ribbed seals can be adjusted on site
- light weight
- Simple installation in the formwork

Scope of delivery:

- 1 piece of wall sleeve with flange
- 3 pieces of 3-ribbed seal
- 2 pieces of closing covers



Dimensions:

- Flange all-around: 50mm

Properties:

- FHRK-certified
- Ready for installation with closing cover
- Dimensionally stable
- resistant to cracking

Application range:

- Water exposure class DIN 18533: W1-E and W2.1-E
- Waterproof concrete stress class 1 and 2

Material:

- Pipe: PVC-U
- Flange: ABS
- 3-ribbed seals: EPDM
- Closing cover: PE

Tightness:

- gastight and watertight

FEATURES

Wall sleeve ID (mm):	200
Wall sleeve OD (mm):	214
:	336
flange surface dimension (mm):	311
Length (mm):	365
Packing unit:	1

PICTURES

