

Membrane injection system

for buildings with a basement

MIS60ND 1x30-34 BL1300 Set10

Article no.: 3030382136, GTIN: 4052487230148



- **no groundwork at the property**
- **universal building entry with membrane injection system for core holes in the most common types of wall**
- **Controlled resin discharge through slotted membrane hose**



Picture may differ from selected product

For reliable sealing of micropipes/ fibre optic cables, telecommunications cables or power cables. Can be used for uncontrolled drilling rockets.

FACTS

Advantages:

- sealing lips ensure gentle seal for cables/pipes
- Variable sealing configuration thanks to pre-mounted sealing inserts

Scope of delivery:

- 1 packing unit:
- 10 pieces of MIS 60ND
- 10 pieces of wall terminator element (only for communication variant)
- 10 pieces of wall rosette (only with electricity variant)
- 10 pieces 2-component resin Resinator, 150 ml
- 1 piece of quick tensioning device MIS60 SVS
- 1 piece of core drill hole cleaning brush MIS REB

Dimensions:

- For core drills Ø: 62 - 65 mm
- For wall thicknesses: from 200 to 1200 mm

Application range:

- Water exposure class DIN 18533: W1-E
- Waterproof concrete stress class 1 and 2

Material:

- Flange, seal insert and counter-bearing: EPDM
- Resin injection hose: PE
- Wall terminator element: Flame-retardant polycarbonate
- Pipe: PVC-U
- Wall rosette: PE
- Quick tensioning device: glass fibre reinforced polyamide/ABS

Tightness:

- gastight and watertight to 1.0 bar

FEATURES

| | |
|-----------------------------------|-------------|
| Number of cables/medium: | 1 |
| suitable for medium pipe OD (mm): | 30 - 34 |
| Overall length (mm): | 1300 |
| Wall thickness (mm): | 200 - 1.200 |