

Fixed/loose flange wall sleeve galvanised

for retrofit dowelling for black tank

FLFA1x250/80/0 DIN18533 St-A3C

Article no.: 3030353454, GTIN: 4052487226905

For fixing in front of wall sleeves, core drills or breakthroughs.



Picture may differ from selected product

FACTS

Scope of delivery:

- 1 piece of fixed/loose flange wall sleeve
- Fastenings for concrete
- Nuts

Dimensions:

- Standard upper length: 80 mm
- Design in accordance with DIN 18533 includes: components in contact with the soil
- Standard fixed flange $\varnothing a$ equal to the relevant wall sleeve $\varnothing i$ + approx. 330 mm (for one passage)

Application range:

- Water exposure class DIN 18533: W1-E, W2.1-E and W2.2-E

Material:

- Fixed/loose flange wall sleeve steel galvanised (gv)
- Fastenings: stainless steel V4A (AISI 316L)
- Nuts: Steel galvanised (gv)


Tightness:

- gastight and watertight

FEATURES

Wall sleeve ID (mm):	250
Fixed flange OD (mm):	580
Loose flange OD (mm):	570
Wall sleeve wall thickness (mm):	2

PICTURES



ACCESSORIES REQUIRED



Rubber inlays