

Single wall insert with foldable rubber sleeve

for setting in concrete and connecting cable ducts

HSI150 1X1 KMA172/200

Article no.: 3030476251, GTIN: 4052487242110



- thanks to the folding sleeve technique, no additional pipe connection components are necessary
- elastic and firmly supported connection due to increased insertion depth, even with deflection of the cable duct
- inside connection option for system seals for cables



Picture may differ from selected product

For the direct connection of cable ducts (exterior) and for connecting system seals for cables (interior).

FACTS

Advantages:

- defined insertion depth of the cable duct through the stop in the sleeve
- Available from wall thicknesses of 120 mm and above
- Quality seal: tightness from the factory. Option to check for accidental or unauthorized opening of the closing cover
- pressure-tight seal to the concrete through 3-ribbed seal, with two 3-ribbed seals from wall thicknesses of 150 mm and above



Scope of delivery:

- 1 piece pressure-tight system cover HSI150 DTS
- 1 piece blind cover
- 2 pieces of HSI150 AH40 spacer
- 1 piece of clamping strap
- when connecting corrugated cable ducts, clip rings must be ordered separately. When ordering, please specify duct type and manufacturer.

Dimensions:

- Frame dimensions: 220x 220 mm
- Centre distance with spacer: 250 mm

Properties:

- FHRK-certified

Application range:

- Waterproof concrete stress class 1 and 2

Material:

- Wall insert: ABS with TPE 3-ribbed seal
- Closing cover: ABS with TPE seal
- Adapter pipe: PVC
- Sleeve: EPDM
- Clamping straps: W4
- Blind cover: PP

Tightness:

- gastight and watertight to 2.5 bar
- radon-proof

FEATURES

:	200
Pipe	
OD:	160-172

PICTURES

